

# HIGH TEMPERATURE DECOMPOSITION OF HYDROGEN PEROXIDE

## PRIORITY CLAIM UNDER 35 U.S.C. § 119(e)

[0001] This application claims priority, under 35 U.S.C. § 119(e), on U.S. Provisional Application No. 60/276,260, filed March 8, 2001.

## ORIGIN OF THE INVENTION

[0002] The invention described herein was made by an employee of the United States Government and may be manufactured and used by or for the Government of the United States of America for governmental purposes without the payment of any royalties thereon or therefor.

## BACKGROUND OF THE INVENTION

### 1. Field of the Invention

[0003] This invention relates generally to a method and apparatus for the high temperature decomposition of hydrogen peroxide to form oxidative free radicals, such as, hydroxyl radical (HO<sup>•</sup>) and hydroperoxyl radical (HOO<sup>•</sup>), which oxidize nitric oxide (NO) to nitrogen dioxide (NO<sub>2</sub>).

### 2. Description of the Background Art

[0004] Power plants produce a large amount of nitric oxide that must be removed from exhaust gas streams before the gas stream may be emitted into the environment. Effective removal of nitric oxide from the gas stream is complicated by its low water solubility. Although water scrubber systems may be used to aid in the removal of nitric oxide from the gas streams, the effectiveness of the water scrubber system may be increased by oxidizing the nitric oxide to nitrogen dioxide. Nitrogen dioxide is more water soluble than nitric oxide and can be easily removed from the gas streams using various removal processes, such as the water scrubber systems. Although nitric oxide does slowly oxidize in air to nitrogen dioxide, an effective oxidizing agent is needed to make the oxidation of nitric oxide effective at low concentrations (~50 to 350 ppm). This low concentration of NO represents a target planned by the US EPA for

power plant applications. By 2004, the EPA will require that coal and oil fired power plants install new controls that lower the NOx emissions to 110 ppm. The 2004 requirement for natural gas NOx emissions will be lowered in 2004 to 50 ppm. Currently, the Selective Catalytic Reduction (SCR) method is the only technology that can meet these 2004 EPA requirements.

5 [0005] Gas-phase oxidation of nitric oxide to nitrogen dioxide may be increased by using ozone, hydrogen peroxide, atomic oxygen, hydroxyl radicals or hydroperoxyl radicals as oxidizing agents. The problems with these materials are their high cost and complexity. Injection of hydrogen peroxide in a heated (300 to 400°C) nitric oxide gas stream or the introduction of an ultraviolet light source to decompose hydrogen peroxide to form oxidative free radicals are examples of known technology with high processing costs. Another expensive material that has been used to oxidize nitric oxide is ozone. A need therefore exists for a highly effective and low cost method for oxidation of nitric oxide.

#### SUMMARY OF THE INVENTION

[0006] To overcome the foregoing problems, the subject invention provides a method and apparatus wherein a hydrogen peroxide solution is directed onto a heated surface in a nitric oxide stream so that the hydrogen peroxide is decomposed to form oxidative free radicals, hydroxyl and hydroperoxyl, for the oxidation of the nitric oxide. The hydrogen peroxide solution is preferably delivered to the heated surface through a nozzle, which may also be heated, to increase the concentration of and thereby enrich the hydrogen peroxide solution. Impinging the enriched hydrogen peroxide solution onto a heated surface accelerates the decomposition of hydrogen peroxide. Because the rapid decomposition of hydrogen peroxide occurs on the heated surface, there is no increased risk of explosion of stored hydrogen peroxide solution. Since the high temperature decomposition of hydrogen peroxide to oxidative free radicals, hydroxyl and hydroperoxyl, occurs in a stream of nitric oxide, distribution of the oxidative free radicals in the stream will cause rapid gas-phase oxidation of the nitric oxide to nitrogen dioxide.

20  
25 [0007] This high temperature decomposition process provides a simple way for increasing the instability of hydrogen peroxide to the point of decomposition. The process only requires a

small pump, a nozzle, a heated surface, and an optional heated tube. There is no need to heat the gas stream that contains the nitric oxide or to introduce an ultraviolet light source or ozone generator.

[0008] This process may be used in small scrubbers or large scrubbers similar to those found in power plants. The basic unit is the same for both applications, but the power plant would use multiple units distributed across the flue stack. The commercial potential for this high temperature decomposition process when used in combination with a wet scrubber for nitrogen dioxide is very large. Power plant applications that control NO<sub>x</sub> emission are estimated to cost in the billions of dollars. This process is the key to making current technology effective in controlling low-level emissions of nitric oxide found in power plants worldwide.

#### BRIEF DESCRIPTION OF THE DRAWINGS

[0009] The features and advantages of the present invention will become apparent from the following detailed description of preferred embodiments thereof, taken in conjunction with the accompanying drawings, in which:

[0010] FIG. 1 illustrates an example of the high temperature decomposition process of the subject invention for hydrogen peroxide;

[0011] FIG. 2 illustrates an embodiment of the present invention for adding hydrogen peroxide to a nitric oxide exhaust gas stream in a power plant;

[0012] FIG. 3 illustrates a laboratory scale apparatus for adding H<sub>2</sub>O<sub>2</sub> to a nitric oxide gaseous stream;

[0013] FIG. 4 illustrates a heated surface having a catalytic coating that is employed in the apparatus of FIG. 3 for injecting and decomposing hydrogen peroxide; and

[0014] FIG. 5 is a graph of Fourier Transform Infrared (FTIR) results of a laboratory scale version of the high temperature decomposition process showing the conversion of nitric oxide to nitric dioxide as measured at the heated surface at temperatures of 25, 200, 225, 250 and 300°C.

#### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0015] In the preferred embodiments of the present invention, high temperature decomposition of hydrogen peroxide to form the oxidative free radicals, hydroxyl and hydroperoxyl, provides a convenient source of highly effective oxidizing agents for the oxidation of nitric oxide in the gas-phase. This high temperature decomposition process avoids problems of complexity and costs common to other methods for the decomposition of hydrogen peroxide.

[0016] An example of the high temperature decomposition process is illustrated in FIG. 1. Prior to impinging a hydrogen peroxide solution 8 (containing hydrogen peroxide and water) onto a heated surface 18, the hydrogen peroxide solution 8 may be optionally heated to vaporize some of the water into steam 12. The hydrogen peroxide solution 8 may be pumped through a tube or nozzle 10. In this example, the hydrogen peroxide solution 8 is heated to ~140°C. If the hydrogen peroxide solution is heated, water in the heated hydrogen peroxide solution 8 evaporates in the form of steam 12 resulting in an enriched hydrogen peroxide solution 14. This enriched hydrogen peroxide solution 14 impinges on the heated surface 18 (preferably heated to 200°-500°C) where oxidative free radicals, hydroxyl and hydroperoxyl, are produced. The decomposition of hydrogen peroxide occurring on the heated surface 18 results in rapid decomposition without increasing the risk of an explosion of the hydrogen peroxide solution 8 that is in storage prior to use. Preferably, the heated surface 18 contains a catalytic coating 20 composed of a variety of compounds including, but not limited to, Fe(II), Fe(III) Cr(II), Cu(II), Pt black, Ag, or Pd. Additionally, the decomposition of hydrogen peroxide may occur on a

variety of catalytic coatings 20 including oxide surfaces, such as metal oxides, glass, quartz, Mo glass,  $\text{Fe}_3\text{-xMn}_x\text{O}_4$  spinels,  $\text{Fe}_2\text{O}_3$  with Cu ferrite, MgO and  $\text{Al}_2\text{O}_3$ . The key element for the high temperature decomposition of hydrogen peroxide is contact with a heated surface 18, regardless of whether the surface has a catalytic coating 20 or not. Table 1 discloses a number of catalytic coatings 20 and the corresponding heated surface temperatures for decomposing hydrogen peroxide. Presently, iron oxide has given the highest degree of conversion.

**Table 1. Catalysts and Conditions Used to Decompose Hydrogen Peroxide**

Catalyst	Conditions
Silver Oxide	250-507°C
Iron Oxide	200-415°C
Ruthenium Oxide	300-491°C
Silver	244-325°C

[0017] The oxidative free radicals are distributed throughout a gaseous nitric oxide stream, preferably containing 50-350 ppm nitric oxide, to rapidly oxidize NO to  $\text{NO}_2$ . Once the NO is oxidized to  $\text{NO}_2$ , it is more water-soluble and can be scrubbed with a wet scrubber system. The heated tube or nozzle 10 and the heated surface 18 could be fabricated as a single unit that is connected to a pump manifold that supplies the hydrogen peroxide and electrical lines that supply the power for electric heaters for the nozzle 10 and heated surface 18.

[0018] The high temperature decomposition process is based on the thermodynamic instability of hydrogen peroxide. High concentrations (over 50%) of hydrogen peroxide in solution are unstable and the rate of decomposition increases by a factor of 2.3 for each 10°C temperature rise. Therefore, a solution containing hydrogen peroxide and water is used in this high temperature decomposition. Preferably, high temperature decomposition may be used to decompose hydrogen peroxide solutions up to and including 50% by weight or volume. However, the hydrogen peroxide solutions do not have to be pre-concentrated.



### Example 1

[0021] A laboratory scale breadboard version of the subject high temperature decomposition process was used to confirm the conversion of NO to NO<sub>2</sub> when exposed to oxidative free radicals generated from the decomposition of hydrogen peroxide on a heated surface having a catalytic coating. In this example, a compressed gas cylinder that contained 5000-ppm nitric oxide in nitrogen was connected to a flow controller adjusted to provide 0.2 liters per minute of the mixture. The output of the flow controller was mixed with the output from a second flow controller that provided 4.8 liters per minute of nitrogen. The resulting mixture, which had a concentration of 200 ppm of NO was introduced into a test fixture 40 as illustrated in FIGs. 3 and 4. The test fixture 40 was fabricated from 2-inch clear PVC tubing that directed the test gas mixture 42 of 200 ppm NO over a mild steel block 44 with a 0.44 square-inch surface area that had an oxidized catalytic coating 45 (iron oxide) or a small stainless steel cup that contained catalytic material. A cartridge heater 46 connected to a variable-voltage transformer (not shown) was inserted into the steel block 44. In addition, a thermocouple 47 was inserted into the steel block 44 to measure the surface temperature. A syringe pump 48 was used to provide a controlled flow of 40-volume percent hydrogen peroxide solution 51, which was delivered at a rate of 1 to 3 milliliter (mL) per hour to a syringe needle 50 that touched the heated steel block 44. The syringe needle 50 was configured so the heated steel block 44 also heated the needle tip, which helped increase the concentration of the hydrogen peroxide solution 51 as it contacted the surface of the heated steel block 44. The conversion of NO to NO<sub>2</sub> was measured at sample point 52 by ASTM Method D-1607 and a Fourier Transform Infrared (FTIR) method developed for this application.

[0022] The FTIR results are summarized in the graph of FIG. 5, where the concentrations of NO, NO<sub>2</sub>, NO plus NO<sub>2</sub>, and hydrogen peroxide are plotted versus the temperature of the heated surface or steel block 44. It can be seen from the data illustrated in FIG. 5 that the concentration of NO decreases as the concentration of NO<sub>2</sub> increases, while the sum of the concentrations remains constant. This constant sum indicates that there is direct conversion of NO to NO<sub>2</sub>,

which was suggested by reactions (2) and (3). These data were generated to illustrate the concept of the high temperature decomposition process and were not intended to provide the optimum conditions for the maximum degree of conversion, which is dependent on the application.

5

Example 2

[0023] For power plant applications the concentration of NO is typically in the 200-300 ppm range, which represents about 90 percent of the total NOx emissions with the remainder being primarily NO<sub>2</sub>. Assuming that the total flow of the gas stream containing NO through the flue gas stack is 1,000,000 cfm, the amount of hydrogen peroxide can be calculated as follows:

at 300 ppm

NO concentration = 300 ppm in 1,000,000 scfm stack gas

Temperature after SOx scrubber 50°C

wt. NO

300 cfm @ 50°C = 254 scfm NO

254 scfm = 391 gm moles NO = 21.2 lbs of NO

$\text{H}_2\text{O}_2 + \text{NO} \rightarrow \text{NO}_2 + \text{H}_2\text{O}$

H<sub>2</sub>O<sub>2</sub> required

1 mole NO reacts with 1 mole H<sub>2</sub>O<sub>2</sub>

Therefore: 21.2 lbs of NO required 24 lbs H<sub>2</sub>O<sub>2</sub>

or 48 lbs at 50 wt % H<sub>2</sub>O<sub>2</sub> or 4.8 gal/min.

20

[0024] This example starts with a 50% hydrogen peroxide solution and passes it through a check valve to prevent back-flow. Then, the hydrogen peroxide solution is heated to raise the temperature to approximately 140°C as illustrated in FIG. 1. The heat vaporizes some of the water in the hydrogen peroxide solution and produces an enriched hydrogen peroxide solution and steam. The steam and the enriched hydrogen peroxide solution are impinged onto a heated (200-500°C) surface. The heated surface in this example is covered by a catalytic coating of

25



iron oxide because it produces a high degree of conversion. The resulting process causes the rapid decomposition of hydrogen peroxide to oxidative free radicals, hydroxyl and hydroperoxyl. These oxidative free radicals are produced in a flowing stream of NO where they rapidly oxidize it to NO<sub>2</sub>.

5 [0025] Although the present invention has been disclosed in terms of a number of preferred embodiments, and variations thereon, it will be understood that numerous additional modifications and variations could be made thereto without departing from the scope of the invention as defined by the following claims.